
Replacement Film Pack for StealthShield Comb Model (2pcs) Instruction for Use EN


General Information

Product Name: StealthShield Model Name: Comb model General Name: Face Shield

Intended Use: Wear on the face to protect splash adhesion Product Category: Personal Protective Equipment (PPE)

Size / Color Variation : F(One size) / Brown Configuration: Film 2 sheets (Frame not included)





Symbol	Description
	Manufacturer
\triangle	Contraindications/Danger/ Warning/Precautions
NON	Non-Sterile
[]i	Read Instruction for Use
EC REP	European Authorized Representative
LOT	Lot Number
REF	Catalog Number
CE	Complies with requirements of EU Regulation 2016/425

How to Assemble

- 1) There is no distinction between 2 sides of the frame.
- 2) Fit the 4 holes of the film to the hooks of the frame respectively.
- 3) Make sure the hole pressed in properly and edge of the hole is flat.





Pinch the handles and put it on the head by spreading it out a

Symbols of labelling

- 5) Adjust the position.
- 6) When taking off the shield, use the handle; when putting away the shield, gently remove the film from the frame.



Warnings and Precautions



Don't use the shield if any component is damaged or disable to replace with new component.

Single use or multiple uses by the same user when disinfected properly.

This shield is supplied clean but NOT sterilized.

Reprocessing Instruction

In case of reuse, after preceding use, disinfect / sterilize in accordance with guidance provided by the CDC and EPA. (https://www.epa.gov/coronavirus/about-list-n-disinfectants-coronavirus-covid-19-0)

Alcohol-based disinfectant may cause cloudy white. Able to wash with detergent, rinse, and wipe off with a soft cloth.

Before reuse, inspect the frame and the film for damage, (cracks, deformation, impaired vision, or improper fit)

Technical & Safety Info.

Element	Attribution
Material (Frame)	polypropylene
Material (Film)	Polyethylene terephthalate
Gases during combustion	Aldehyde gas
Ignition Temp (Frame)	130°C / 266°F
Ignition Temp (Film)	300°C / 572°F
Disposal Method	Follow Local regulation



Manufacturer Info.

CHARMANT INC.

6-1 Kawasari-cho, Sabae-city, Fukui-pref. 916-8555 JAPAN Phone. 0120-180807(JP) / +1-973-867-2450 (US) medical@charmant.co.jp www.charmant.com





USE CASE





Clinic



Nursing



School



Barber



Esthetic



Transport



Deliverery



Shop



Restaurant



Reception



Meeting